



Technical Data Sheet

ORBIPUTZ

DESCRIPTION Orbiputz is a decorative scratched and full effect acrylic-siloxane plaster with fibers which makes it self washable, longer life and better pigment preservation in the long term. It is applied on normal surfaces and walls that are covered with layers of silicate based, it is used on interior and exterior walls. It has a high resistance on different weather conditions, moisture, scratches and small cracking's. It is transpiring and lets the wall breathe. It preserves the color better because of the main ingredient of pure acryl.



APPLICATION Areas in which we will apply Orbiputz must have a sound base, clean and dry. Before applying Orbiputz, it is suggested to apply two basic hands of Primer FA, especially when we are dealing with gypsum surface, skimmed, concrete, etc. On the painted walls, it is suggested to eliminate mechanically the old paint and plaster, in particular the old and damaged parts. After the preparation and cleaning it should be applied Primer FA. In case of tinting the Orbiputz, it is suggested that the Primer FA to be tinted on a close color and then Orbiputz is applied as a final hand. Application of Orbiputz is made with either metallic or plastic trowel depending on the effect you want to achieve. It is suggested that the application of Orbiputz should be at temperatures above 5 degrees Celsius and relative humidity up to 70%. Do not apply on rainfall and wind blows.

PRODUCT DATA Package: 25kg / 24 pieces per pallet
Storage: In a dry place in the original package. Protect the product from freezing and direct sunlight.

CONSUMPTION The consumption of Orbiputz per Square Meter depends on the thickness and the surface that it will be applied:

1.0 mm	~1.0-1.1 kg/m ²
1.5 mm	~1.0-1.2 kg/m ²
2.0 mm	~1.5-1.7 kg/m ²
2.5 mm	~1.7-2.0 kg/m ²

DRYING 12-24 hours. It also depends on the weather conditions, temperature, and air humidity.

SAFETY Please refer to our safety data sheet for information relating to product safety.