



Maxx White Interior - Exterior

Water-based paint based on acrylic synthetic resins, of excellent quality, suitable for interior and exterior building surfaces.

High-performance coating with excellent hiding power, high whiteness and reflectance, as well as excellent resistance to washing and adverse weather conditions.

It provides a smooth matt finish with an outstanding aesthetic result, while allowing the substrate to breathe.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Excellent whiteness
- ✓ Excellent wet scrub resistance
- ✓ Very good coverage
- ✓ Easy application
- ✓ Does not chalk

SURFACES / USES

- ✓ Concrete
- ✓ Plasterboard
- ✓ Plaster
- ✓ Brick
- ✓ Wood

TECHNICAL DATA

Appearance	Viscous liquid
Coverage	11-13 m ² /lt per coat
Density	≤ 1,60 kg/l
Thinning	5-10% with water
pH	8-9
Binder	Acrylic
Touch dry	30-45 min
Viscosity	9000 - 11000 mPa·s at 23°C
Recoating time	3-4 hr
Wet scrub resistance (EN 13300 / ISO 11998)	Class 2
Gloss Level (ISO 2813:2014)	Matt

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

Apply to dry, clean surfaces, free from any materials that may impair adhesion. Successful application depends on proper substrate preparation and correct application of the product. Prime the surface with ACRYL BOND or water-based DESMO SEAL.



Application

Once the primer begins to dry, apply MAXX WHITE in two coats. To adjust the application viscosity, dilute with 5-10% water. Apply the second coat after the first coat has dried.



Storage

Shelf life: one year in the original sealed container when stored at temperatures between 5°C and 35°C.



VOC Category

Product category A/c (WB): "Exterior walls of mineral substrate" in accordance with European Directive 2004/42/EC. EU limit value for this product category: 40 g/L. Maximum VOC content of the ready-to-use product: 39 g/L. Contains a biocidal product. Contains C(M)IT/MIT (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.



Tools Cleaning

During application, keep the tools wet by leaving them in the paint container or tray. Drain any excess paint thoroughly back into the container and clean the tools with water.



Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the relative humidity exceeds 80%. Damp surfaces must be allowed to dry thoroughly before application.