



Prestige Aqua

Water-based enamel paint

PRESTIGE AQUA water-based enamel is an odourless, premium-quality coating for wooden surfaces, ideal for both interior and exterior use. It offers excellent adhesion and is suitable for repainting previously painted surfaces. It provides exceptional whiteness and does not yellow over time. It is easy to apply, with excellent flow and levelling properties, high hiding power and a flawless finish.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Non-yellowing
- ✓ Fast drying
- ✓ Excellent opacity
- ✓ UV resistant

SURFACES / USES

- ✓ Metal
- ✓ Wood
- ✓ Plastic
- ✓ Wall

TECHNICAL DATA

Shade	White and various shades
Coverage	9-13 m ² /lt per coat
Thinning	5-8% with Water
Touch dry	1-2hr
Viscosity	4000 - 6000 mPa·s at 23°C
Recoating time	6-8 hrs
pH	8-9
Gloss level according to ISO 2813:2014	Mid Sheen
Pyknometer Cup ISO 2811: 2011 Method	≤ 1,30 kg/L

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Successful application depends on proper substrate preparation and correct application of the material.
- Wooden surfaces should be primed with Velatura Aqua water-based undercoat and metal surfaces with Antirust.



Application

- Apply Prestige Aqua water-based enamel paint in two coats.
- To adjust viscosity, it may be diluted with 5-8% water.
- The second coat should be applied after the first coat has dried.
- Wooden surfaces should be primed with Velatura Aqua water-based undercoat and metal surfaces with Antirust.



Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the relative humidity exceeds 80%. Allow damp surfaces to dry thoroughly before application. Protect the freshly painted surface from cold and moisture for at least 24 hours.



Tools Cleaning

During application, keep tools "wet" inside the container or paint tray. Drain the paint thoroughly from the tools back into the tin and clean them with water.



Storage

Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.



Precautions

It poses no risk to human health or the environment.



VOC Category

Product category A/d (WB): "Interior/exterior trim and cladding points for wood and metal" according to European Directive 2004/42/EC. EU limit value for this product category: 130 g/L (2010). Maximum VOC content of the ready-to-use product: 129 g/L.