



Prestige

Solvent-based enamel paint

High-quality solvent-based synthetic-resin enamel. Provides exceptional, long-lasting whiteness and gloss together with excellent hiding power. Suitable for metal, wood and wall surfaces, both indoors and outdoors. Easy to apply, with excellent flow and levelling. Available in gloss white, matt white, black and 38 ready-mixed shades.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ High gloss and hiding power
- ✓ UV resistant
- ✓ High coverage
- ✓ Excellent flow and levelling
- ✓ High flexibility

SURFACES / USES

- ✓ Metal
- ✓ Wood
- ✓ Cement

TECHNICAL DATA

Thinning	3% with Brush Thinner
Touch dry	3-4hr
Recoating time	24hr
Shade	Various colours
Viscosity	1500 - 2000 mPa·s at 23°C
Fineness Of Grid ISO 1524: 2013	≤ 10 microns
Density (ISO 2811: 2011)	≤ 1,20 kg/L
Gloss (ISO 2813: 2014)	Gloss

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any material that may impair adhesion.
- Successful application depends on correct substrate preparation and proper application of the product.
- Remove silicone or oil contamination from the metal surface with thinner.
- Prime metal surfaces with one or two coats of ANTIRUST or IRON GUARD metal primer.
- Prime wooden surfaces with one or two coats of VELATURA.



Application

- Once the primer has dried, apply PRESTIGE enamel in two coats.
- To adjust the application viscosity, thin with 3% white spirit.
- Apply the second coat after the first coat has dried.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

While working, keep the tools 'wet' in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with White Spirit.



Storage

Store for up to one year in a sealed container at temperatures between 5°C and 40°C.



VOC Category

Product category A/d (SB): "Interior/exterior trim and cladding paints for wood and metal" in accordance with European Directive 2004/42/EC. EU limit value for this product category: 300 g/L (2010). Maximum VOC content of the ready-to-use product: 299 g/L.