



2 to 1 Varnish & Protective

Alkyd-based coating for interior and exterior wooden surfaces. It combines the benefits of a wood varnish and a wood preservative.

It protects the wood against the growth of microorganisms, weathering and UV radiation.

Thin with BRUSH THINNER.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ High gloss
- ✓ Long-lasting durability
- ✓ Excellent finish
- ✓ High spreading rate
- ✓ Easy to apply
- ✓ Resistant to UV radiation
- ✓ Resistant to the growth of microorganisms

SURFACES / USES

- ✓ Ideal for:
- ✓ Wooden surfaces

TECHNICAL DATA

Appearance	Liquid
Shade	Transparent
Coverage	12-14m ² /lt per coat
Density	0.95 ± 0.02 gr/cm ³
Thinning	5% with White Spirit
Binder	Alkyd
Touch dry	3-4hr
Ideal application and drying temperature	15 - 25°C
Viscosity	100-300 mPa·s at 23°C
Through dry	24hr
Solids by weight	55%
Gloss	91
Recoating time	24hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

Apply to dry, clean surfaces free from contaminants that may impair adhesion. Successful application depends on correct substrate preparation and application of the product.



Application

Apply one or two coats of 2 IN 1 WOOD VARNISH & PRESERVATIVE. To adjust the viscosity, thin with 5% BRUSH THINNER. Apply the second coat once the first coat has dried completely.



Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the relative humidity exceeds 80%. Allow damp surfaces to dry thoroughly before application. Protect the freshly painted surface from cold and moisture for at least 24 hours.



Tools Cleaning

During application, keep tools "wet" inside the container or paint tray. Drain the paint thoroughly from the tools back into the tin and clean them with nitro thinner.



Storage

Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.



Precautions

Flammable liquid and vapour. Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.



VOC Category

Product category A/e (SB): "Interior/exterior trim varnishes and woodstains, including opaque woodstains", in accordance with European Directive 2004/42/EC. VOC limit value for this category: 400 g/L. Maximum VOC content of the ready-to-use product: 399 g/L.