



Antimould Ultra

Anti-mould additive and primer

Special additive for water-based emulsion paints and distempers.

When added to paint, it imparts anti-mould properties and helps prevent the growth of mould and the unsightly black staining that develops on walls due to microorganisms.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Protection against mould and fungi on ceilings and walls
- ✓ Compatible with emulsion and acrylic paints
- ✓ Does not alter colour shades
- ✓ Improves adhesion

SURFACES / USES

- ✓ Cement
- ✓ Plaster
- ✓ Concrete
- ✓ Plasterboard
- ✓ Cement board

TECHNICAL DATA

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Wall surfaces containing loose or unsound material, oil, grease, salts or dust, surfaces affected by mould or fungi, and surfaces previously coated with glue paint, distemper or limewash that are blistering or flaking must be thoroughly abraded and cleaned.
- After cleaning, rinse the surfaces with clean water and allow them to dry completely.



Application

- Add ANTIMOULD ULTRA to emulsion or acrylic paint as an anti-mould performance additive.
- It may also be used as a masonry primer with anti-mould and antifungal properties.



Storage

- Store containers in a cool, dry place at temperatures between 5°C and 40°C. Protect containers from direct sunlight.



Tools Cleaning

- Remove as much material as possible from the tools before cleaning.
- Clean tools immediately after use with a solution of water and detergent.



VOC Category

- Product of Category A/g (WB) "Primers" of European Directive 2004/42 / EC. Category VOC limit value: 30gr/lit. The maximum VOC content of the ready-to-use product is 29gr/lit.