



Antirust

Anti-Corrosive Metal Primer

High-quality, fast-drying anticorrosive primer suitable for metal surfaces. It provides effective protection against corrosion and rust, excellent adhesion, high hiding power, flexibility, and excellent flow and levelling.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ High adhesion
- ✓ Excellent opacity
- ✓ High anti-corrosion protection
- ✓ High coverage

SURFACES / USES

- ✓ Metal

TECHNICAL DATA

Appearance	Viscous liquid
Shade	White, black, grey, terracotta
Coverage	10-12m²/lit per coat
Density	1.50 ± 0,02 gr/cm³
Thinning	5% with Brush Thinner
Binder	Alkyd
Touch dry	1hr
Ideal application and drying temperature	15 – 25°C
Viscosity	2000-2500 mPa·s at 23°C
Through dry	24hr
Solids by weight	73%
Recoating time	24hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Successful application depends on proper substrate preparation and correct application of the material.
- Remove silicone or oils from the metal surface using thinner.



Application

- Prime the surface with two coats of Antirust metal primer.
- To adjust viscosity, it may be diluted with 5% white spirit.
- The second coat should be applied after the first coat has dried.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

- During application, keep tools "wet" inside the container or paint tray.
- Drain the paint thoroughly from the tools back into the tin and clean them with white spirit.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.



VOC Category

- Product of Category A / i (SB) "One-pack performance coatings" of European Directive 2004/42 / EC. Category VOC limit value: 500gr/lit. The maximum VOC content of the ready-to-use product is 499gr/lit.