



Betocryl W200

Solvent-Based Acrylic Masonry Paint

Solvent-based acrylic concrete paint for the effective protection of roof tiles, walls and floors. It offers excellent adhesion, high hiding power and an outstanding finish, while protecting surfaces against corrosion, weathering and atmospheric pollution.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Weather resistant
- ✓ High coverage
- ✓ Excellent hardness
- ✓ Excellent chemical resistance

SURFACES / USES

- ✓ Ideal for surfaces of:
- ✓ Concrete
- ✓ Plaster
- ✓ Bricks

TECHNICAL DATA

Shade	White, Grey, Blue
Coverage	11-13 m ² /lt per layer
Density	1.50 ± 0,02 gr/cm ³
Thinning	5-10% with BRUSH SOLVENT SL-100 (White Spirit)
Recoating time	6-8hr
Touch dry	30min
Viscosity	7500 - 8000 mPa.s at 23°C
Gloss	20-40

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

It is applied on dry, clean surfaces free of materials that prevent adhesion. Application's success depends on the proper preparation of the surface and the correct application of the material. For highly absorbent surfaces, prime surface with DESMO SEAL solvent-based primer.



Application

BETOCRYL W-200 is applied directly to the concrete surface with a dilution of 15-20% with BRUSH SOLVENT SL-100 (White spirit). Then Apply BETOCRYL W-200 on the surface in two layers. To adjust the fluidity, it can be diluted by adding 5-10% BRUSH SOLVENT SL-100 (White spirit). The second layer must be applied after the first one has dried.



Storage

One year in closed container, at temperatures between 5°C - 40°C.



VOC Category

Product of Category A/c (SB) "Exterior walls of mineral substrate" of European Directive 2004/42 / EC. Category VOC limit value: 430gr/lt. The maximum VOC content of the ready-to-use product is 429gr/lt.



Tools Cleaning

While working, keep the tools "wet" in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with White Spirit.



Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the air relative humidity is higher than 80%. Wet surfaces should be allowed to dry thoroughly before application. Freshly painted surface should be protected from cold and moisture for at least 24hr.