



Chalk Paint

Chalk Paint

Water-based decorative paint that creates a matt finish and a wide range of decorative effects, including two-tone and vintage-style finishes. Ideal for restoring and decorating wooden furniture, walls and objects made from various materials, such as wood, metal, plastic, upholstery, brick, cement, etc.

It can be applied directly to any surface, including old surfaces previously coated with paint or varnish, without any surface preparation, sanding or priming.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Decorative finish
- ✓ High spreading rate
- ✓ Easy to spread

SURFACES / USES

- ✓ Ideal for surfaces of:
- ✓ Concrete
- ✓ Plaster
- ✓ Wood
- ✓ Bricks
- ✓ Glass
- ✓ Plastic
- ✓ Metal

TECHNICAL DATA

Appearance	Viscous liquid
Shade	White
Coverage	10-12m ² /lt per coat
Density	1.55 ± 0,02 gr/cm ³
Thinning	5-10% with water
pH	8-9
Viscosity	7500 - 8000 mPa·s at 23°C
Binder	Acrylic
Touch dry	30min
Through dry	3hr
Recoating time	4-6hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

It is applied on dry, clean surfaces free of materials that prevent adhesion. Application's success depends on the proper preparation of the surface and the correct application of the material.



Application

Apply CHALK PAINT on the surface in two layers. The second layer must be applied after the first one has dried. To adjust the fluidity, it can be diluted by adding 5-10% water.



Storage

One year in closed container, at temperatures between 5°C - 40°C.



Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the air relative humidity is higher than 80%. Wet surfaces should be allowed to dry thoroughly before application. Freshly painted surface should be protected from cold and moisture for at least 24hr.



Tools Cleaning

While working, keep the tools "wet" in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with water.



Precautions

CONTAINS BIOCIDAL PRODUCTS: Contains C(M)IT/MIT (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.



VOC Category

Product of Category A/a (WB) "Interior matt walls and ceilings (Gloss <25@60°)" of European Directive 2004/42 / EC. Category VOC limit value: 30gr/lt. The maximum VOC content of the ready-to-use product is 29gr/lt.