



Chalkboard Paint

Chalkboard Paint

ChalkBoard Paint is a high-quality acrylic paint that transforms any interior surface into a chalkboard. It offers a simple, easy and creative way to personalise any space, including children's rooms, where children can safely write and draw on it with chalk.

It dries quickly and provides a smooth, uniform finish with excellent wash resistance. It is odourless, ammonia-free and can be cleaned with soap and water.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Decorative finish
- ✓ Easy application
- ✓ Excellent wash resistance
- ✓ User-friendly

SURFACES / USES

- ✓ Concrete
- ✓ Wood
- ✓ Plaster

TECHNICAL DATA

Appearance	Viscous liquid
Shade	Black, green
Coverage	10-12m ² /lt per coat
Density	1,30 ± 0,05 gr/cm ³
Thinning	5-10% with Water
pH	8-9
Touch dry	30min
Viscosity	7500-8000 mPa·s at 23°C
Recoating time	4-6hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Successful application depends on proper substrate preparation and correct application of the material.
- Clean the surface from foreign particles, dust and residues.



Application

- Apply Chalkboard Paint in two coats.
- To adjust viscosity, it may be diluted with 5-10% water.
- The second coat should be applied after the first coat has dried.



Restrictions

Do not apply at temperatures below 5°C or above 35°C.
Do not apply when the relative humidity exceeds 80%.
Allow damp surfaces to dry thoroughly before application.
Protect the freshly painted surface from cold and moisture for at least 24 hours.



Tools Cleaning

During application, keep tools "wet" inside the container or paint tray.
Drain the paint thoroughly from the tools back into the tin and clean them with water.



Storage

Store for up to one year in the original sealed container at temperatures between 5°C and 35°C.



VOC Category

Product category A/d (WB): "Interior/exterior trim and cladding paints for wood, metal or plastic", in accordance with European Directive 2004/42/EC. VOC limit value for this category: 130 g/L. Maximum VOC content of the ready-to-use product: 30 g/L.