



Chassi Lux 2 in 1

2-In-1 Metal Paint And Primer

High-gloss paint for new metal surfaces, ideal for vehicle chassis. Suitable for railings, garage doors, agricultural machinery, commercial vehicles, etc. It offers excellent flexibility and outstanding resistance to petroleum products, lubricants, washing and impact.

Priming is generally not required. It provides excellent anticorrosive protection and an attractive finish that retains its gloss and colour over time.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Excellent opacity
- ✓ Anti-corrosion protection
- ✓ High coverage
- ✓ Very good mechanical resistance

SURFACES / USES

- ✓ Metal

TECHNICAL DATA

Appearance	Viscous liquid
Shade	Various colours
Coverage	12-14m ² /lt per coat
Density	1.35 ± 0,02 gr/cm ³
Thinning	5% with white spirit
Touch dry	2hr
Viscosity	2000-2500 mPa.s at 23°C
Recoating time	24hr
Through dry	24hr
Ideal application and drying temperature	15-25°C
Solids by weight	62%

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Successful application depends on proper substrate preparation and correct application of the material.
- Remove any silicone or oils from the metal surface using thinner.



Application

- Prime the surface with two coats of Chassi-Lux.
- To adjust viscosity, it may be diluted with 5% white spirit.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

- During application, keep tools "wet" inside the container or paint tray.
- Drain the paint thoroughly from the tools back into the tin and clean them with white spirit.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 35°C



Chassi Lux 2 in 1

2-In-1 Metal Paint And Primer

APPLICATION TOOLS



PACKAGING



Precautions

- Flammable liquid and vapour. Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.
- If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection. Store locked up. May produce an allergic reaction. POISON CENTRE: 210 779 3777.



VOC Category

Product of Category A / i (SB) * One-pack performance coatings of European Directive 2004/42 / EC. Category VOC limit value: 500gr/lt. The maximum VOC content of the ready-to-use product is 499gr/lt.