



Classic


Solvent-Based General-Purpose Wood Varnish

High-quality transparent wood varnish for interior and exterior use. It provides a high-gloss finish and long-lasting durability. Suitable for all wooden surfaces, including doors, windows, frames, handrails, garden furniture and wood panelling. It waterproofs the surface and provides effective protection against UV radiation, thanks to its specially selected UV filters and pigments.

APPLICATION TOOLS



PACKAGING





Classic

Solvent-Based General-Purpose Wood Varnish

Its high flexibility allows it to accommodate the natural movement of the wood. Available in clear and nine shades.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ High gloss
- ✓ Excellent finish
- ✓ Easy to spread
- ✓ Great elasticity

SURFACES / USES

- ✓ Ideal for surfaces of:
- ✓ Wood

TECHNICAL DATA

Shade	Transparent
Coverage	12-14m ² /lt per coat
Density	0.95 ± 0.02 gr/cm ³
Thinning	5% with White Spirit
Gloss	95
Recoating time	24hr
Touch dry	3-4 hr
Viscosity	100 - 300 mPa·s at 23°C

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

It is applied on dry, clean surfaces free of materials that prevent adhesion. Application's success depends on the proper preparation of the surface and the correct application of the material. For complete protection, one to two coats of EPIXYL are recommended before applying the varnish.



Application

Apply CLASSIC WOOD VARNISH on the surface in two coats. The second layer must be applied after the first one has dried. To adjust the fluidity, it can be diluted by adding 5% White Spirit.



Storage

One year in closed container, at temperatures between 5°C - 35°C.



Tools Cleaning

During application, keep the tools wet by leaving them in the container or paint tray. Drain as much paint as possible from the tools back into the container, then clean them with white spirit or nitro thinner.



Classic

Solvent-Based General-Purpose Wood Varnish

APPLICATION TOOLS



PACKAGING



Precautions

• Flammable liquid and vapour. Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

Repeated exposure may cause skin dryness or cracking.

• If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection. Store locked up. Dispose of contents/container in accordance with national and local regulations.

CONTAINS: Cobalt bis(2-ethylhexanoate). May produce an allergic reaction.
POISON CENTRE: 210 779 3777.

Restrictions

Do not apply at temperatures below 5°C or above 35°C
Do not apply when the air relative humidity is higher than 80%

Wet surfaces should be allowed to dry thoroughly before application.

Freshly painted surface should be protected from cold and moisture for at least 24hr.

VOC Category

Product of Category A/e (SB) "Interior/exterior trim varnishes and woodstains, including opaque woodstains" of European Directive 2004/42 / EC. Category VOC limit value: 400gr/lt. The maximum VOC content of the ready-to-use product is 399gr/lt.