



Color Restorer

Surface reviver and protective treatment

Clear, penetrating impregnating oil that restores the original colour and sheen of faded surfaces.

Easy to apply, it revives dull surfaces. It penetrates the substrate without forming a film and offers excellent weather resistance.

APPLICATION TOOLS



PACKAGING

CHARACTERISTICS

- ✓ Restores the original colour and sheen of faded surfaces
- ✓ Deep penetrating and silicone-free
- ✓ Protects against corrosion and wear
- ✓ Easy to apply, with a durable finish

SURFACES / USES

- ✓ Metal
- ✓ Plastic
- ✓ Wood
- ✓ Stone

TECHNICAL DATA

Coverage	14 - 16m ² /lt per coat
Thinning	Ready to use
Touch dry	2-3hr
Recoating time	4-6hr
Appearance	Low-viscosity liquid
Shade	Transparent
Density	0,84 ± 0,02 gr/cm ³
Viscosity	30-50 sec at 23°C

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any material that may impair adhesion.
- Stir thoroughly before use.



Application

- Apply COLOR RESTORER unthinned in one coat using a brush or sponge.
- Remove any excess material with a dry cloth 10-20 minutes after application.



Tools Cleaning

- Drain the material thoroughly from the tools back into the tin and clean them with water.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Storage

- Store for up to one year in a sealed container at temperatures between 5°C and 35°C.