



Contact Adhesive

Contact Adhesive

Multi-purpose adhesive, ideal for bonding a wide variety of different materials and surfaces.

Its excellent quality ensures strong adhesion, long-lasting durability and ease of application.

APPLICATION TOOLS



PACKAGING

CHARACTERISTICS

- ✓ Excellent adhesion
- ✓ Long-lasting durability
- ✓ High spreading rate
- ✓ Easy to apply

SURFACES / USES

- ✓ Ideal for bonding:
- ✓ Leather
- ✓ Rubber
- ✓ Wood
- ✓ Panels
- ✓ Chipboard

TECHNICAL DATA

Appearance	Liquid
Shade	Beige
Density	0,95 ± 0,02 gr/cm³
Binder	Vinyl-based polymer
Ideal application and drying temperature	15 – 25°C
Viscosity	15000 mPa·s at 23°C
Solids by weight	67%

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

Apply to dry, clean surfaces free from contaminants that may impair adhesion. Successful application depends on correct substrate preparation and application of the product.



Application

Apply the adhesive to the surface to be bonded. Press the two surfaces firmly together and maintain pressure for 5-10 minutes. Ensure that the two surfaces are securely bonded. Release the applied pressure.



Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the relative humidity exceeds 80%. Allow damp surfaces to dry thoroughly before application. Protect the treated surface from cold and moisture for at least 24 hours.



Tools Cleaning

Clean the tools with nitro thinner.



Storage

Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.



VOC Category

Exempt