



Deck Oil

Solvent-Based Protective Varnish For Wooden Floors

Polyurethane-modified protective penetrating oil, enhanced with wax, for interior and exterior wooden decking. It penetrates deep into the pores of the wood, waterproofing and protecting it against UV radiation and harsh weather conditions. It offers excellent resistance to chemicals, weathering and mechanical wear.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Polyurethane-modified
- ✓ Enriched with wax
- ✓ Protects wooden decking
- ✓ Resistant to intense sunlight and moisture

SURFACES / USES

- ✓ Wood

TECHNICAL DATA

Appearance	Liquid
Shade	Transparent
Coverage	12-16m ² /lt per coat
Density	0.85 ± 0.02 gr/cm ³
Thinning	Ready for use
Touch dry	2-3hr
Viscosity	200-500 mPa·s at 23°C
Recoating time	24-48hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Successful application depends on proper substrate preparation and correct application of the material.



Application

- Apply Deck Oil in one coat. Wipe off any excess material after 5 minutes using a dry cloth.
- A second coat should be applied on very hard woods or where the wood is exposed to severe weather conditions.
- The second coat should be applied after the first coat has dried.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

- During application, keep tools "wet" inside the container or paint tray. Drain the material thoroughly from the tools back into the tin and clean them with thinner.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 35°C.



VOC Category

- Product category A/h (SB): "Binding primers", in accordance with European Directive 2004/42/EC. VOC limit value for this category: 750 g/L. Maximum VOC content of the ready-to-use product: 749 g/L.