



Deco Plast

Odourless Emulsion Paint

Premium-quality emulsion paint with high hiding power and exceptional whiteness, providing excellent results with easy application. Ideal for interior areas requiring frequent repainting and refreshing.

Suitable for plaster, concrete, exposed concrete, skim-coated surfaces, etc. Its specially developed formulation helps protect both the user and the environment during application.

Its formulation contains no hazardous substances, heavy metals, formaldehyde, ammonia or aromatic hydrocarbons.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ High whiteness
- ✓ Excellent wet-scrub resistance
- ✓ High spreading rate
- ✓ High hiding power
- ✓ Easy to apply

SURFACES / USES

- ✓ Ideal for surfaces of:
- ✓ Concrete
- ✓ Plaster
- ✓ Bricks
- ✓ Wood

TECHNICAL DATA

Shade	White
Coverage	10-12 m ² /lt per layer
Density	1.50 ± 0,02 gr/cm ³
Thinning	5-10% with water
pH	8-9
Recoating time	3-4hr
Touch dry	30-45min
Viscosity	7500 - 8000 mPa·s at 23°C
Appearance	Viscous liquid

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

It is applied on dry, clean surfaces free of materials that prevent adhesion. Application's success depends on the proper preparation of the surface and the correct application of the material. The surface is primed with either DESMO SEAL water-based primer or ACRYL BOND primer.



Application

Apply DECO PLAST on the surface in two layers. To adjust the fluidity, it can be diluted by adding 5-10% water. The second layer must be applied after the first one has dried.



Storage

One year in closed container, at temperatures between 5°C - 40°C.



Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the air relative humidity is higher than 80%. Wet surfaces should be allowed to dry thoroughly before application.



Tools Cleaning

While working, keep the tools "wet" in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with water.



Precautions

CONTAINS A BIOCIDAL PRODUCT: Contains C(M)IT/MIT (3:1) and BIT. May produce an allergic reaction. Safety data sheet available on request.



VOC Category

Product of Category A/a (WB) "Interior matt walls and ceilings (Gloss <25@60°)" of European Directive 2004/42 / EC. Category VOC limit value: 30gr/lt. The maximum VOC content of the ready-to-use product is 29gr/lt.