



Deco XYL

Water-Based Impregnating Wood Varnish With Wax

Water-based acrylic coating for interior and exterior wooden surfaces.

It provides a smooth, transparent, high-gloss finish of excellent aesthetic quality, while waterproofing and protecting the surface against UV radiation and weathering.

Thin with water.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ High gloss
- ✓ Long-lasting durability
- ✓ Excellent finish
- ✓ High coverage
- ✓ Easy to apply
- ✓ Resistant to UV radiation

SURFACES / USES

- ✓ Ideal for porous surfaces of:
- ✓ Wood

TECHNICAL DATA

Appearance	Liquid
Coverage	12-14m ² /lt per coat
Thinning	10% with water
Shade	Transparent
Recoating time	6-8 hr
Touch dry	1-2 hr
Viscosity	100-300 mPa·s at 23°C
Through dry	24hr
Binder	Acrylic
Ideal application and drying temperature	15-25°C
Solids by weight	55%
Gloss	81
Density	1,01 ± 0,02 gr/cm ³

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any materials that may impair adhesion.
- Successful application depends on proper substrate preparation and correct application of the product.



Application

- Apply ECO XYL varnish in one or two coats.
- For complete protection, apply one or two coats of Super Base water-based wood preservative before applying ECO XYL varnish.
- To adjust the viscosity, thin with up to 10% water.
- Apply the second coat once the first coat has dried completely.



Storage

- Store in a tightly closed container at temperatures between 5°C and 40°C.



VOC Category

Product category A/e (WB): "Interior/exterior trim varnishes and woodstains, including opaque woodstains", in accordance with European Directive 2004/42/EC. VOC limit value for this category: 130 g/L. Maximum VOC content of the ready-to-use product: 129 g/L.



Tools Cleaning

During application, keep the tools wet by leaving them in the container or paint tray. Drain as much paint as possible from the tools back into the container, then clean them with water.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity exceeds 80%.
- Damp surfaces must be allowed to dry thoroughly before application.
- The freshly coated surface must be protected from cold and moisture for at least 24 hours.