



Desmo Contact

Quartz Adhesion Primer For Smooth Surfaces

Ready-to-use, water-based acrylic quartz primer, ideal for interior and exterior surfaces.

It is designed for smooth substrates where a textured surface is required to enhance adhesion before applying plaster, render or microcement. It is alkali-resistant and allows the substrate to breathe.

It improves the appearance, coverage, adhesion and durability of the plaster or render.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Excellent adhesion
- ✓ High hiding power
- ✓ High spreading rate
- ✓ Easy to apply

SURFACES / USES

- ✓ Ideal for porous surfaces of:
- ✓ Concrete
- ✓ Gypsum board
- ✓ Plaster
- ✓ Bricks
- ✓ Wood

TECHNICAL DATA

Shade	White, terracotta
Coverage	300-350 gr/m ² per coat
Density	1.32 ± 0,02 gr/cm ³
Thinning	Ready for use
pH	8-9
Touch dry	1-2hr
Viscosity	7000-8000 mPa·s at 23°C
Appearance	Viscous liquid
Recoating time	24-36 hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any materials that may impair adhesion.
- Successful application depends on proper substrate preparation and correct application of the product.
- Remove all foreign particles, dust and residues from the surface.



Application

The surface is primed in one layer with DESMO CONTACT textured primer in such a way as to maintain its "embossed" texture. After 24-36 hours the final plaster is applied according to its specifications.



Storage

One year in closed container, at temperatures between 5°C - 40°C.



Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the air relative humidity is higher than 80%. Wet surfaces should be allowed to dry thoroughly before application. Freshly painted surface should be protected from cold and moisture for at least 24hr.



Tools Cleaning

While working, keep the tools "wet" in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with water.



Precautions

CONTAINS BIOCIDAL PRODUCTS: Contains C(M)IT/MIT (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.



VOC Category

Product of Category A/g (WB) "Primers" of European Directive 2004/42 / EC. Category VOC limit value: 30gr/lit. The maximum VOC content of the ready-to-use product is 29gr/lit.