



Desmo Seal Aqua

Transparent, 100% acrylic water-based primer with excellent penetrating properties. It strengthens and stabilises surfaces prior to painting while reducing their absorbency. Formulated with special acrylic resins that waterproof the substrate.

Virtually odourless, it penetrates deeply and stabilises the surface. An ideal primer for emulsion and acrylic paints, textured coatings, concrete paints and waterproofing coatings.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ High penetrating power
- ✓ Excellent alkali resistance
- ✓ Waterproofs surfaces

SURFACES / USES

- ✓ Concrete
- ✓ Plasterboard
- ✓ Plaster
- ✓ Brickwork

TECHNICAL DATA

Appearance	Liquid
Shade	Transparent
Coverage	16-18m ² /lt per coat
Density	1.01 ± 0.02 gr/cm ³
Thinning	50-100% with water
pH	8-9
Touch dry	30min
Viscosity	50-150 mPa·s at 23°C
Recoating time	3-4hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

Apply to dry, clean surfaces free from any materials that may impair adhesion. Successful application depends on proper substrate preparation and correct application of the product. Remove all foreign particles, dust and residues from the surface.



Application

Prime the surface with DESMO SEAL WATER-BASED PRIMER. Once the primer begins to dry, apply the topcoat according to its application instructions. Depending on the absorbency of the surface, the primer may be thinned with 50-100% water.



Tools Cleaning

During application, keep tools "wet" inside the container or paint tray. Drain the paint thoroughly from the tools back into the tin and clean them with brush thinner.



Precautions

CONTAINS A BIOCIDAL PRODUCT: Contains C(M)IT/MIT (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.



Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the relative humidity exceeds 80%. Damp surfaces must be allowed to dry thoroughly before application.



Storage

One year in closed container, at temperatures between 5°C - 40°C.



VOC Category

Product of Category A/g (WB) "Primers" of European Directive 2004/42 / EC. Category VOC limit value: 30gr/lt. The maximum VOC content of the ready-to-use product is 29gr/lt.