



Elite

Plastic primer

Water-based, high-hiding primer for exterior and interior building surfaces.

Improves the adhesion of the finish coat to the substrate and enhances its appearance and hiding power.

Virtually odourless, it penetrates and stabilises the surface.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Odourless
- ✓ For interior and exterior use
- ✓ Penetrates and stabilises the surface
- ✓ Improves adhesion of the finish coat

SURFACES / USES

- ✓ Concrete
- ✓ Plasterboard
- ✓ Plaster
- ✓ Brick
- ✓ Wood

TECHNICAL DATA

Coverage	9 – 11 m ² /lt per coat
Thinning	5-10% with Water
Touch dry	20min
Recoating time	2hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any material that may impair adhesion.
- Successful application depends on correct substrate preparation and proper application of the product.
- Remove all foreign matter, dust and residues from the surface.



Application

- Prime the surface with two coats of ELITE WALL PRIMER.
- Apply the second coat after the first coat has dried.
- Once the primer begins to dry, apply the finish coat in accordance with its product specification.
- To adjust the application viscosity, thin with 5-10% water.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.
- Protect the freshly painted surface from cold and moisture for at least 24 hours.



Tools Cleaning

During application, keep tools wet in the container or paint tray. Drain as much paint as possible from the tools back into the tin, then clean them with water.



Storage

Store in a sealed container at temperatures between 5°C and 40°C.



Precautions

CONTAINS A BIOCIDAL PRODUCT: Contains C(M)IT/MIT (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety Data Sheet available on request.



VOC Category

Product category A/g (WB), 'Primers', in accordance with European Directive 2004/42/EC. VOC limit for this category: 30 g/L. Maximum VOC content of the ready-to-use product: 29 g/L.