



Epi XYL

Solvent-Based Impregnating Wood Varnish

Transparent wood preservative for interior and exterior use. It protects the wood against the growth of microorganisms, moisture and UV radiation.

Its flexible finish accommodates the natural expansion and contraction of the wood without peeling, blistering or cracking. Available in clear and nine shades.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Easy to spread
- ✓ Resistance to microorganisms' growth
- ✓ Follows the contractions and expansions of the wood

SURFACES / USES

- ✓ Ideal for surfaces of:
- ✓ Wood

TECHNICAL DATA

Shade	Transparent
Coverage	10-12m ² /lt per coat
Density	0.81 ± 0,02 gr/cm ³
Thinning	5% with brush thinner or spray-gun thinner
Viscosity	200 - 500 mPa·s at 23°C
Touch dry	1-2 hr
Recoating time	24 hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

It is applied on dry, clean surfaces free of materials that prevent adhesion. Application's success depends on the proper preparation of the surface and the correct application of the material.



Application

Apply EPIXYL WOOD PROTECTIVE on the surface in one or two coats. To adjust the fluidity, it can be diluted by adding 5% White Spirit.



Storage

One year in closed container, at temperatures between 5°C - 35°C.



Tools Cleaning

While working, keep the tools "wet" in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with White Spirit.



Precautions

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Store locked up. Dispose of contents/container in accordance with national and local regulations.

Contains: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%).

CONTAINS: 3-Iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

POISON CENTRE: 210 779 3777.



Epi XYL

Solvent-Based Impregnating Wood Varnish

APPLICATION TOOLS



PACKAGING



Restrictions

Do not apply at temperatures below 5°C or above 35°C
Do not apply when the air relative humidity is higher than 80%
Wet surfaces should be allowed to dry thoroughly before application.
Freshly painted surface should be protected from cold and moisture for at least 24hr.

VOC Category

Product of Category A/f (SB) 'Interior and exterior minimal build woodstains' of European Directive 2004/42 / EC.
Category VOC limit value: 700gr/lt. The maximum VOC content of the ready-to-use product is 699gr/lt.