



Hy-Primo

Water-based hybrid polyurethane primer

HY-PRIMO is a water-based hybrid primer for use before the application of waterproofing systems. It penetrates, waterproofs and stabilises the application surface, including cracked substrates. It provides strong adhesion to concrete, bituminous membranes, cement boards, acrylic and polyurethane coatings, and similar surfaces. Its very low VOC content makes it low-odour and user-friendly. Ready to use. Strong adhesion

APPLICATION TOOLS



PACKAGING





Hy-Primo

Water-based hybrid polyurethane primer

Fast drying
Low odour
Ready to use

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Excellent primer for waterproofing systems
- ✓ Strong adhesion
- ✓ Fast drying
- ✓ Low odour
- ✓ Ready to use

SURFACES / USES

- ✓ Concrete
- ✓ Plasterboard
- ✓ Plaster
- ✓ Brick

TECHNICAL DATA

Coverage	16 - 18 m ² /lt per coat
Thinning	Ready to use
Touch dry	30min
Recoating time	3hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any material that may impair adhesion.
- Successful application depends on correct substrate preparation and proper application of the product.
- Remove all foreign matter, dust and residues from the surface.



Application

- Prime the surface with one coat of HY-DESMO SEAL.
- Once the primer begins to dry, apply the finish coat in accordance with its product specification.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.
- Protect the freshly painted surface from cold and moisture for at least 24 hours.



Tools Cleaning

During application, keep tools wet in the container or paint tray. Drain as much paint as possible from the tools back into the tin, then clean them with water.



Storage

Store in a sealed container at temperatures between 5°C and 40°C.



VOC Category

Product of Category A/g (WB) "Primers" of European Directive 2004/42 / EC. Category VOC limit value: 30gr/lt. The maximum VOC content of the ready-to-use product is 29gr/lt.