



Ideal

Ready-Mixed Acrylic Skim Filler

Ideal Acrylic Skim Filler is a high-quality, ready-to-use filler, suitable for smoothing interior and exterior surfaces such as concrete, render and wood.

It is easy to work with and sands down easily.

Apply with a spatula on clean surfaces, free from dust and foreign substances.

It dries in approximately 1-2 hours, depending on conditions.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ High adhesion
- ✓ Moisture resistant
- ✓ High coverage
- ✓ Easy application

SURFACES / USES

- ✓ Interior and exterior surfaces
- ✓ Skim coating
- ✓ Filling

TECHNICAL DATA

Appearance	Paste
Shade	White
Density	1,8 ± 0,02 gr/cm³
pH	8.0-9.0
Binder	Acrylic
Ideal application and drying temperature	15 – 25°C
Viscosity	500000-550000 mPa.s at 23°C

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Successful application depends on proper substrate preparation and correct application of the material.



Application

- Apply with a spatula without dilution.
- Sand after 2-3 hours using sandpaper.
- Once cleaned, it can be painted with cement paints, emulsion paints or water-based paints.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.
- Protect the treated surface from cold and moisture for at least 24 hours.



Tools Cleaning

- Clean tools with water.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.



VOC Category

- Exempt