



Metal Glaze

Metal Varnish

Metal Glaze is a high-quality transparent protective varnish for metal surfaces, suitable for interior and exterior use.

It provides high gloss and long-lasting durability.

It waterproofs and effectively protects metal from sunlight, while enhancing anti-corrosive protection.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Polyurethane enamel paint
- ✓ High gloss and hardness
- ✓ UV resistant
- ✓ High coverage

SURFACES / USES

- ✓ Metal

TECHNICAL DATA

Shade	Transparent
Coverage	12-14m ² /lt per coat
Density	0.92 ± 0.02 gr/cm ³
Thinning	5% with Brush Thinner
Touch dry	3-4hr
Viscosity	1250 - 2500 mPa·s at 23°C
Gloss	95
Recoating time	24hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Successful application depends on proper substrate preparation and correct application of the material.
- Remove any silicone or oils from the metal surface using thinner.



Application

- Apply Metal Glaze varnish in two coats.
- To adjust viscosity, it may be diluted with 5% brush thinner.
- The second coat should be applied after the first coat has dried.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

- During application, keep tools "wet" inside the container or paint tray.
- Drain the paint thoroughly from the tools back into the tin and clean them with white spirit or nitro thinner.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.



VOC Category

- Product of Category A/e (SB) "Interior/exterior trim varnishes and woodstains, including opaque woodstains" of European Directive 2004/42 / EC. Category VOC limit value: 400gr/lt. The maximum VOC content of the ready-to-use product is 399gr/lt.