



# Paint Glue

## Paint Glue

Cellulose-based adhesive, ideal for preparing fillers and reinforcing cement mortars. Its excellent quality ensures strong adhesion, long-lasting durability and excellent workability.

### APPLICATION TOOLS



### PACKAGING



### CHARACTERISTICS

- ✓ Excellent adhesion
- ✓ Long-lasting durability
- ✓ High spreading rate
- ✓ Easy to apply

### SURFACES / USES

- ✓ Ideal for:
- ✓ Preparing fillers
- ✓ Reinforcing cement mortars
- ✓ Bonding wallpaper

### TECHNICAL DATA

|                                          |                    |
|------------------------------------------|--------------------|
| Appearance                               | Powder             |
| Shade                                    | Beige              |
| Density                                  | 1,05 ± 0,02 gr/cm³ |
| Binder                                   | Methylcellulose    |
| Ideal application and drying temperature | 15 – 25°C          |
| Viscosity                                | 4000 mPa.s at 23°C |
| Solids by weight                         | 100%               |

(\*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



#### Surface Preparation

Apply to dry, clean surfaces free from contaminants that may impair adhesion. Successful application depends on correct substrate preparation and application of the product.



#### Application

Mix the adhesive with filler and water to prepare a skim-coat filler. Apply it to the surface to be filled. Add the adhesive to the cement mortar you wish to reinforce. For wallpaper application, mix the adhesive with water and apply it to the surface to be covered.



#### Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the relative humidity exceeds 80%. Allow damp surfaces to dry thoroughly before application. Protect the treated surface from cold and moisture for at least 24 hours.



#### Tools Cleaning

Clean tools with water.



#### Storage

Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.



#### Precautions

Not classified as hazardous to human health or the environment.



#### VOC Category

Exempt