



Parquet Aqua Varnish

Water-Based Parquet Varnish

Water-based acrylic varnish for wooden floors. It provides a smooth, transparent, high-gloss finish of excellent aesthetic quality, protecting the floor against abrasion, scratching, water and detergents.

Thin with water.

It offers excellent resistance to abrasion and detergents, while protecting and enhancing the natural appearance of the floor.

It dries quickly and is available in gloss or matt finish.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ High gloss
- ✓ Long-lasting durability
- ✓ Excellent finish
- ✓ High spreading rate
- ✓ Easy to apply
- ✓ Excellent abrasion and mechanical resistance

SURFACES / USES

- ✓ Wooden floors

TECHNICAL DATA

Appearance	Liquid
Shade	Transparent
Coverage	10-12m ² /lt per coat
Density	1.03 ± 0.02 gr/cm ³
Thinning	5% with Water
Touch dry	1-2hr
Viscosity	200-500 mPa·s at 23°C
Gloss	83
Recoating time	6-8hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Successful application depends on proper substrate preparation and correct application of the material.



Application

Prime the surface with one or two coats of PARQUET AQUA PRIMER. To adjust the viscosity, thin with up to 5% water. Apply the second coat once the first coat has dried completely.



Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the relative humidity exceeds 80%. Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

During application, keep tools "wet" inside the container or paint tray. Drain the paint thoroughly from the tools back into the tin and clean them with water.



Storage

Store for up to one year in the original sealed container at temperatures between 5°C and 35°C.



VOC Category

Product category A/I (WB): "One-pack performance coatings" under European Directive 2004/42/EC. Category VOC limit: 140 g/L. Maximum VOC content of the product ready for use: 139 g/L.