



Plaster Contact

Quartz Bonding Primer For Renders

Ready-to-use, water-based acrylic textured primer. It creates a rough, textured key on the substrate, improving the adhesion, coverage and durability of decorative render.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Strong adhesion
- ✓ Enhances the adhesion of plaster
- ✓ High spreading rate
- ✓ Ready to use

SURFACES / USES

- ✓ Ideal for porous surfaces of:
- ✓ Concrete
- ✓ Gypsum board
- ✓ Plaster
- ✓ Bricks
- ✓ Wood

TECHNICAL DATA

Shade	White
Coverage	150-200 gr/m ² per layer
Density	1.34 ± 0,02 gr/cm ³
Thinning	Ready for use
pH	8-9
Viscosity	4000-5000 mPa.s at 23°C
Touch dry	45-60 min
Recoating time	4-6 hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

It is applied on dry, clean surfaces free of materials that prevent adhesion. • Application's success depends on the proper preparation of the surface and the correct application of the material.



Application

The surface is primed in one or two layers (depending on the absorbency of the substrate) with PLASTER CONTACT textured primer in such a way as to maintain its 'embossed' texture. • After 4-6 hours the final plaster is applied according to its specifications.



Storage

One year in closed container, at temperatures between 5°C - 40°C.



VOC Category

Product of Category A/g (WB) "Primers" of European Directive 2004/42 / EC. Category VOC limit value: 30gr/ltr. The maximum VOC content of the ready-to-use product is 29gr/ltr.
Ready-to-use acrylic textured water-based primer. Used on surfaces where roughness must be created in order to enhance the adhesion, coverage and durability of the decorative plaster. It is suitable for use in external thermal insulation composite systems (ETICS), as well as in indoor and outdoor masonry surfaces.



Tools Cleaning

While working, keep the tools 'wet' in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with water.



Restrictions

• Do not apply at temperatures below 5°C or above 35°C • Do not apply when the air relative humidity is higher than 80% • Wet surfaces should be allowed to dry thoroughly before application.