



Prestige Acrylic

Solvent-Based Enamel Paint

100% acrylic white paint for exterior surfaces, offering excellent resistance to harsh weather conditions. Ideal for easy maintenance and repainting. Provides high whiteness and excellent colour retention.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ High whiteness
- ✓ Weather resistance
- ✓ Very good performance
- ✓ High spreading rate
- ✓ Easy to spread

SURFACES / USES

- ✓ Ideal for surfaces of:
- ✓ Concrete
- ✓ Plaster
- ✓ Wood
- ✓ Bricks

TECHNICAL DATA

Shade	White
Coverage	10-12m ² /lt per coat
Density	1.52 ± 0,02 gr/cm ³
Thinning	5-10% with water
pH	8-9
Viscosity	7500 - 8000 mPa.s at 23°C
Touch dry	30-45min
Recoating time	3-4hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

It is applied on dry, clean surfaces free of materials that prevent adhesion. Application's success depends on the proper preparation of the surface and the correct application of the material. The surface is primed with Desmo Seal solvent-based primer.



Application

Apply PRESTIGE ACRYLIC on the surface in two layers. The second layer must be applied after the first one has dried. To adjust the fluidity, it can be diluted by adding 5-10% water.



Storage

One year in closed container, at temperatures between 5°C - 40°C.



Restrictions

Do not apply at temperatures below 5°C or above 35°C. Do not apply when the air relative humidity is higher than 80%. Wet surfaces should be allowed to dry thoroughly before application. Freshly painted surface should be protected from cold and moisture for at least 24hr.



Tools Cleaning

While working, keep the tools 'wet' in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with water.



Precautions

CONTAINS A BIOCIDAL PRODUCT: Contains C(M)IT/MIT (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.



VOC Category

Product of Category A/c (WB) "Exterior walls of mineral substrate" of European Directive 2004/42 / EC. Category VOC limit value: 40gr/lt. The maximum VOC content of the ready-to-use product is 39gr/lt.