



Prestige Interior

Premium emulsion paint

Premium-quality, odourless emulsion paint formulated with high-grade polymer emulsions for maximum hiding power and durability. Resistant to fading caused by sunlight and washing.

Suitable for interior and exterior surfaces.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Excellent hiding power
- ✓ High tinting strength
- ✓ Wet-scrub resistant
- ✓ High coverage
- ✓ Easy application

SURFACES / USES

- ✓ Concrete
- ✓ Plasterboard
- ✓ Plaster
- ✓ Brick
- ✓ Wood

TECHNICAL DATA

Coverage	11-13m ² /lt per coat
Thinning	5-10% with Water
Touch dry	30-45min
Recoating time	3-4hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any material that may impair adhesion.
- Successful application depends on correct substrate preparation and proper application of the product.
- Remove all foreign matter, dust and residues from the surface.
- Prime the surface with either ACRYL BOND emulsion primer or DESMO SEAL solvent-thinnable primer.



Application

- Once the primer begins to dry, apply PRESTIGE INTERIOR emulsion paint in two coats.
- To adjust the application viscosity, thin with 5-10% water.
- Apply the second coat after the first coat has dried.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

- During application, keep tools wet in the container or paint tray. Drain as much paint as possible from the tools back into the tin, then clean them with water.



Storage

- Store in a sealed container at temperatures between 5°C and 40°C.



VOC Category

Product category A/a (WB), 'Interior matt walls and ceilings (gloss ≤25 at 60°)', in accordance with European Directive 2004/42/EC. VOC limit for this category: 30 g/L. Maximum VOC content of the ready-to-use product: 29 g/L.