



Rust Converter

Rust converter

Powerful rust converter that is easy to apply and restores rusted surfaces to a sound, stable condition.

It forms a protective blue-black film that inhibits corrosion, increases the mechanical strength of the metal surface and provides longer-lasting protection.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Stabilises rust
- ✓ Protects metal against corrosion
- ✓ Easy to use

SURFACES / USES

- ✓ Metal

TECHNICAL DATA

Coverage	14-18 m ² /lt
Density	1.35 ± 0,02 gr/cm ³
pH	1-2
Touch dry	2-3hr
Viscosity	30 – 50 sec at 23°C
Recoating time	24hr
(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.	



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Stir well before use.



Application

- Rust Converter is applied in one coat without dilution.
- Remove any excess material with a dry cloth.
- After 24 hours, apply an anti-rust primer and paint for full protection of the metal surface.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

- Drain the material thoroughly from the tools back into the tin and clean them with water.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.