



Silverlux 300°C

Heat-resistant aluminium paint, up to 300°C

Alkyd-based coating for metal surfaces. Produces a smooth, high-gloss finish with an excellent aesthetic appearance and is available in a wide range of shades. Thin with NITRO THINNER.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ High gloss
- ✓ Very good hiding power
- ✓ Excellent finish
- ✓ High coverage
- ✓ Easy application
- ✓ Very good temperature resistance

SURFACES / USES

- ✓ Ideal for surfaces of:
- ✓ Metal

TECHNICAL DATA

Coverage	14 - 16m ² /lt per coat
Thinning	5% with Nitro Thinner
Touch dry	2-3hr
Through dry	24hr
Recoating time	24hr
Appearance	Low-viscosity liquid
Shade	Silver
Density	0,95 ± 0,02 gr/cm ³
Binder	Alkyd
Viscosity	500-1000 mPa·s at 23°C
Ideal application and drying temperature	15-25°C
Solids by weight	50%
Gloss	89

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any material that may impair adhesion.
- Successful application depends on correct substrate preparation and proper application of the product.
- Remove silicone or oil contamination from the metal surface with thinner.



Application

- Apply SILVERLUX aluminium enamel in one or two coats.
- To adjust the application viscosity, thin with 5% NITRO THINNER.
- Apply the second coat after the first coat has dried.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.
- Protect the freshly painted surface from cold and moisture for at least 24 hours.



Tools Cleaning

While working, keep the tools 'wet' in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with Nitro Thinner.



Storage

- Store in a sealed container at temperatures between 5°C and 40°C.



Silverlux 300°C

Heat-resistant aluminium paint, up to 300°C

APPLICATION TOOLS



PACKAGING



Precautions

- Flammable liquid and vapour. Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Toxic to aquatic life with long-lasting effects.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Wash hands thoroughly after handling. Avoid release to the environment. Wear protective gloves and eye/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.



VOC Category

Product category A/d (SB), 'Interior/exterior trim and cladding paints for wood and metal', in accordance with European Directive 2004/42/EC. VOC limit for this category: 300 g/L (2010).