



SL 100

White Spirit brush thinner

Aliphatic hydrocarbon mixture used as white spirit for thinning alkyd-based paints.

Ideal for cleaning tools.

It helps alkyd coatings dry evenly and achieve an excellent final result.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Uniform drying
- ✓ Low toxicity
- ✓ Low evaporation rate, ideal for high-quality enamels and varnishes

SURFACES / USES

- ✓ Alkyd-based paints
- ✓ Enamels
- ✓ Anti-corrosive primers
- ✓ Undercoats
- ✓ Chassis coatings
- ✓ Stone varnishes
- ✓ For greater safety, always check the technical data sheet or product label before thinning the paint.

TECHNICAL DATA

Appearance	Liquid
Shade	Transparent
Density	0.72± 0,02 gr/cm³
pH	Not applicable
Upper flammability limit	72 % (v/v)
Initial boiling point	135°C
Binder	Aliphatic hydrocarbons
Viscosity	9.18cSt at 40°C
Vapour pressure	0,23 kPa
Flash point	38.5°C
Lower flammability limit	0.6 % (v/v)

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- A metal surface can be cleaned from oils and foreign impurities using SL 100 brush thinner.



Application

- Add SL 100 brush thinner after the alkyd coating has first been mixed evenly.
- Add the appropriate quantity depending on the desired workability.
- Stir until the entire quantity in the container is fully homogenised.



Restrictions

- Do not smoke while using this product.
- Store and use away from heat, sparks, open flames and other ignition sources.
- Keep out of reach of children.



Tools Cleaning

- During application, keep tools "wet" inside the container or paint tray.
- Drain the paint thoroughly from the tools back into the tin and clean them with SL 100 brush thinner.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.



SL 100

White Spirit brush thinner

APPLICATION TOOLS



PACKAGING



Precautions

Flammable liquid and vapour. Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Wash hands thoroughly after handling. Avoid release to the environment. Wear protective gloves/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER/doctor.



VOC Category

Not subject to Directive 2004/42/EC.