



SL 502

General-purpose spray thinner

Fast-drying thinner based on aromatic hydrocarbons.

Its composition helps alkyd coatings dry evenly and quickly, delivering an excellent final result.

For professional use only.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Uniform drying
- ✓ High solubility
- ✓ High evaporation rate ideal for quick-drying enamels

SURFACES / USES

- ✓ Ideal for solvent-based coatings:
- ✓ Alkyd based
- ✓ Enamels
- ✓ Quick drying primers
- ✓ Chassis-coats

TECHNICAL DATA

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

Clean metal surface from oils and foreign impurities using the Thinner SL-502.



Application

- Add Thinner SL-502 after first mixing the coating evenly.
- Add the appropriate amount depending on the desired workability.
- Stir until all the amount in the container is completely homogenous.



Storage

One year in closed container, at temperatures between 5°C - 40°C.



VOC Category

Does not fall under legislation 2004/42/EC.



Tools Cleaning

While working, keep the tools "wet" in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with Thinner SL-502.



Restrictions

- Do not smoke while using the product.
- Store it and use it away from heat sources, sparks, flames, etc.
- Store it out of the reach of children.