



SL 90

Acetone

100% acetone thinner.

Its composition helps alkyd coatings dry evenly and quickly, delivering an excellent final result.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Uniform drying
- ✓ Low toxicity
- ✓ High evaporation rate, ideal for fast-drying enamel paints

SURFACES / USES

- ✓ Alkyd-based paints
- ✓ Cellulose paints
- ✓ Quick-drying anti-corrosive primers
- ✓ Chassis coatings
- ✓ For greater safety, always check the technical data sheet or product label before thinning the paint.

TECHNICAL DATA

Appearance	Liquid
Shade	Transparent
Density	0.79± 0,05 gr/cm³
pH	Not applicable
Upper explosive limit	13 % (v/v)
Initial boiling point	55.8°C
Binder	Ketone
Viscosity	32mPas at 40°C
Vapour pressure	233 hPa
Flash point	<-18°C
Auto-ignition temperature	456°C
Freezing point	94,7°C
Lower explosive limit	2,6 % (v/v)

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- A metal surface can be cleaned from oils and foreign impurities using SL 90 acetone thinner.



Application

- Add SL 90 acetone thinner after the alkyd coating has first been mixed evenly.
- Add the appropriate quantity depending on the desired workability.
- Stir until the entire quantity in the container is fully homogenised.



Restrictions

- Do not smoke while using this product.
- Store and use away from heat, sparks, open flames and other ignition sources.
- Keep out of reach of children.



Tools Cleaning

- During application, keep tools "wet" inside the container or paint tray.
- Drain the paint thoroughly from the tools back into the tin and clean them with SL 90 acetone thinner.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.



SL 90

Acetone

APPLICATION TOOLS



PACKAGING



Precautions

Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.



VOC Category

Not subject to Directive 2004/42/EC.