



Stain Blocker Aqua

Water-based stain-blocking primer

Solvent-based acrylic stain-blocking primer for building surfaces. Isolates smoke, dirt, mould, grease, moisture and similar stains and helps prevent them from reappearing. Provides high whiteness and hiding power, together with excellent adhesion to walls, wood and similar surfaces.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Blocks stains
- ✓ Helps prevent stains from reappearing
- ✓ Maximum hiding power

SURFACES / USES

- ✓ Concrete
- ✓ Plasterboard
- ✓ Plaster
- ✓ Wood

TECHNICAL DATA

Coverage	11-13m ² /lt per coat
Thinning	5-15% with water
Touch dry	1-2hr
Recoating time	6-8hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any material that may impair adhesion.
- Successful application depends on correct substrate preparation and proper application of the product.
- Remove all foreign matter, dust and residues from the surface.



Application

- Prime the surface with one coat of STAIN BLOCKER AQUA.
- For difficult stains, apply a second coat of STAIN BLOCKER AQUA after 24 hours.
- To adjust the application viscosity, thin with 5-15% water.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

During application, keep tools wet in the container or paint tray. Drain as much paint as possible from the tools back into the tin, then clean them with BRUSH THINNER.



Storage

Store for up to one year in a sealed container at temperatures between 5°C and 40°C.



VOC Category

Product category A/g (WB), 'Primers', in accordance with European Directive 2004/42/EC. VOC limit for this category: 30 g/L. Maximum VOC content of the ready-to-use product: 29 g/L. CONTAINS A BIOCIDAL PRODUCT: Contains C(M)IT/MIT (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety Data Sheet available on request.