



Start-X Professional

Professional emulsion paint

Emulsion paint based on highly durable binders. It offers very good hiding power and high whiteness for excellent results with easy application.

Ideal for professional use in areas that require frequent painting and refreshing of interior spaces.

Reliable, guaranteed results, with fast drying and recoating.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Provides a matt finish
- ✓ Resistant to wet scrubbing
- ✓ High coverage
- ✓ Easy application

SURFACES / USES

- ✓ Concrete
- ✓ Plasterboard
- ✓ Plaster
- ✓ Brick
- ✓ Wood

TECHNICAL DATA

Appearance	Viscous liquid
Shade	White
Coverage	11-13m ² /lt per coat
Density	1.55 ± 0,02 gr/cm ³
Thinning	5-10% with Water
pH	8-9
Binder	PVA-VEOVA
Touch dry	30min
Ideal application and drying temperature	15 - 25°C
Viscosity	7500 - 8500 mPa·s at 23°C
Through dry	4hr
Solids by weight	66 %
Recoating time	3hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Successful application depends on proper substrate preparation and correct application of the material.
- Clean the surface from foreign particles, dust and residues.
- Prime the surface with two coats, using either plastic primer or solvent-thinnable Desmo Seal primer.



Application

- Once the primer begins to dry, apply Start-X Professional emulsion paint in two coats.
- To adjust viscosity, it may be diluted with 5-10% water.
- The second coat should be applied after the first coat has dried.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.
- Protect the freshly painted surface from cold and moisture for at least 24 hours.



Tools Cleaning

- During application, keep tools "wet" inside the container or paint tray.
- Drain the paint thoroughly from the tools back into the tin and clean them with water.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.



Precautions

- CONTAINS: reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC No. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC No. 220-239-6] (3:1). May produce an allergic reaction.



VOC Category

- Product of Category A/a (WB) "Interior matt walls and ceilings (Gloss <25@60°)" of European Directive 2004/42 / EC. Category VOC limit value: 30gr/lt. The maximum VOC content of the ready-to-use product is 29gr/lt.