



Super Cover

High-opacity plasterboard primer

Premium-quality plasterboard primer. Emulsion undercoat for unpainted building surfaces such as cement, plaster and plasterboard. Provides very good adhesion and flexibility and creates a uniform substrate for excellent paint flow and levelling. Ideal for interior and exterior use.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Uniform application
- ✓ High hiding power
- ✓ Does not cause finish coats to yellow
- ✓ Smooths imperfections in surfaces to be painted

SURFACES / USES

- ✓ Concrete
- ✓ Plasterboard
- ✓ Plaster
- ✓ Brick

TECHNICAL DATA

Coverage 10-14m²/lt per coat

Thinning 5-10% with Water

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any material that may impair adhesion.
- Successful application depends on correct substrate preparation and proper application of the product.
- Prime the surface with SUPER COVER.



Application

- Once the primer has dried, apply AMBIENTE in two coats.
- To adjust the application viscosity, thin with 5-10% water.
- Apply the second coat after the first coat has dried.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

During application, keep tools wet in the container or paint tray. Drain as much paint as possible from the tools back into the tin, then clean them with BRUSH THINNER.



Storage

Store in a sealed container at temperatures between 5°C and 40°C.



VOC Category

Product category A/a (WB), 'Interior matt coatings for walls and ceilings', in accordance with European Directive 2004/42/EC. VOC limit for this category: 30 g/L. Maximum VOC content of the ready-to-use product: 29 g/L.