



Super Wood

Crystal furniture adhesive

Water-based crystal-clear adhesive for woodworking applications.

Based on a vinyl acetate and styrene copolymer, it ensures excellent adhesion and long-lasting durability on wooden surfaces.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Strong bonding
- ✓ Long-lasting durability
- ✓ High coverage
- ✓ D2 category

SURFACES / USES

- ✓ Wood
- ✓ Paper

TECHNICAL DATA

Appearance	Viscous liquid
Shade	White
Coverage	4-5m ² /lt
Density	1,05 ± 0,02 gr/cm ³
Thinning	Ready to use
pH	4,5-5,0
Binder	Vinyl acetate-styrene copolymer
Ideal application and drying temperature	15 – 25°C
Viscosity	650000 15000 mPa·s at 23°C
Solids by weight	50%
Recoating time	4-6hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Successful application depends on proper substrate preparation and correct application of the material.



Application

- Apply Superwood adhesive with a brush or paintbrush.
- Hold the two surfaces firmly together, applying pressure for 5-10 minutes.
- Make sure that the two surfaces have bonded.
- Release the pressure applied to both sides.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.
- Protect the treated surface from cold and moisture for at least 24 hours.



Tools Cleaning

- Drain the adhesive thoroughly from the tools back into the tin and clean them with water.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 40°C.



Precautions

- Not classified as hazardous to human health or the environment.



VOC Category

- Exempt