



Teak Oil

A blend of natural oils enhanced with wax, designed for interior and exterior wooden surfaces. It refreshes, maintains and protects hardwoods such as teak, oak, Oregon pine, mahogany, etc.

It penetrates deep into the pores of the wood without forming a surface film, prevents water penetration and enhances the wood's natural beauty.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Blend of natural oils
- ✓ Enriched with wax
- ✓ Does not form a surface film
- ✓ Easy to apply

SURFACES / USES

- ✓ Wood

TECHNICAL DATA

Appearance	Liquid
Shade	Transparent
Density	0,85 ± 0,02 gr/cm³
Viscosity	200-500 mPa·s at 23°C
Coverage	14 - 16m²/ltr per coat
Thinning	Ready to use
Touch dry	4-6hr
Recoating time	48 hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any materials that may impair adhesion.
- Successful application depends on proper substrate preparation and correct application of the product.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

- During application, keep the tools wet by leaving them in the container or paint tray. Drain as much material as possible from the tools back into the container, then clean them with a suitable thinner.



VOC Category

Product category A/e (WB): "Interior/exterior trim varnishes and woodstains, including opaque woodstains", in accordance with European Directive 2004/42/EC. VOC limit value for this category: 130 g/L. Maximum VOC content of the ready-to-use product: 129 g/L.

CONTAINS A BIOCIDAL PRODUCT: Contains C(M)IT/MIT (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.



Application

- Apply one coat of TEAK OIL. Wipe off any excess material after 5 minutes using a dry cloth.
- Apply a second coat to very hard woods or where the wood is exposed to harsh weather conditions.
- Apply the second coat once the first coat has dried completely.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 35°C