



Ultra Roof

Elastomeric acrylic roof waterproofing coating

Economical elastomeric acrylic waterproofing coating for flat roofs.

Suitable for waterproofing new roofs and renovation projects.

Provides a cost-effective way to extend the service life of existing waterproofing systems.

Forms a continuous, flexible, watertight and water-vapour-permeable membrane without seams or joints.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Weather resistant without remaining tacky
- ✓ Flexible
- ✓ Easy application

SURFACES / USES

- ✓ Flat roofs

TECHNICAL DATA

Coverage	2-3m ² /lt per coat
Thinning	5-10% with Water
Touch dry	2-3hr
Recoating time	24hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply to dry, clean surfaces free from any material that may impair adhesion.
- Successful application depends on correct substrate preparation and proper application of the product.
- Remove all foreign matter, dust and residues from the surface.
- Prime the surface with solvent-based DESMO SEAL primer.



Application

- Once the primer has dried, apply ULTRA ROOF in two cross coats.
- Apply the second coat 24 hours after the first coat, once the first coat has dried.
- To adjust the application viscosity, thin with 5-10% water.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.
- Protect the freshly painted surface from cold and moisture for at least 24 hours.



Tools Cleaning

During application, keep tools wet in the container or paint tray. Drain as much paint as possible from the tools back into the tin, then clean them with water.



Storage

Store in a sealed container at temperatures between 5°C and 40°C.



VOC Category

Product of Category A/c (WB) "Exterior walls of mineral substrate" of European Directive 2004/42 / EC. Category VOC limit value: 40gr/lt. The maximum VOC content of the ready-to-use product is 39gr/lt.