



Velatura

Solvent-based undercoat

Ideal undercoat for enamels, suitable for wooden and skim-coated surfaces.

It provides a matt finish with high whiteness and excellent hiding power. It is easy to work with, offers excellent flow and levelling, and sands easily.

APPLICATION TOOLS



PACKAGING



CHARACTERISTICS

- ✓ Excellent opacity
- ✓ High whiteness
- ✓ High coverage
- ✓ Easy sanding

SURFACES / USES

- ✓ Wood

TECHNICAL DATA

Appearance	Viscous liquid
Shade	White
Coverage	16-18m ² /lt per coat
Density	1.55 ± 0,02 gr/cm ³
Thinning	3% with Brush Thinner
Touch dry	2-3hr
Viscosity	3000 - 3500 mPa·s at 23°C
Recoating time	12-14hr

(*) Exact drying times depend on the ambient temperature and relative humidity during application and drying.



Surface Preparation

- Apply on dry, clean surfaces, free from materials that may prevent adhesion.
- Successful application depends on proper substrate preparation and correct application of the material.



Application

- Prime the surface with one or two coats of Velatura.
- To adjust viscosity, it may be diluted with 3% white spirit.
- Once the primer has dried, apply the final coating according to its specifications.



Restrictions

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity exceeds 80%.
- Allow damp surfaces to dry thoroughly before application.



Tools Cleaning

- During application, keep tools "wet" inside the container or paint tray.
- Drain the paint thoroughly from the tools back into the tin and clean them with white spirit.



Storage

- Store for up to one year in the original sealed container at temperatures between 5°C and 35°C



VOC Category

- Product category A/h (SB): "Binding primers" under European Directive 2004/42/EC. Category VOC limit: 350 g/L. Maximum VOC content of the product ready for use: 349 g/L.